

1 PORTS VDSL2 ROUTER

(Artikel-Nr. 113544_2)



HARDWARE INTERFACE

- 1 Power Jack
- 1 Power switch to power on/off device
- 1 Reset button to factory defaults
- 1 RJ11 phone jacks for ADSL connection
- 1 Ethernet jack for LAN port connection
- CE/ROHS compliant

VDSL2 / ADSL2+

- ITU-T G.992.5 ADSL2+
- ITU-T G.992.1, G.992.2, G.992.3
- ANSI T1.413 Issue 2
- G.993.2 (VDSL2)
- G.994.1 (G.hs)
- VDSL Profile up to 30a supported
- Data Transmission Rate: Upstream up to 100 Mbps / Downstream: Up to 100 Mbps
- Interoperable with all major DSLAM equipment's

MANAGEMENT

- Web-based for remote and local management
- Firmware upgrades through FTP, TFTP and HTTP
- Embedded Telnet Remote management
- Embedded diagnostic Tool
- TR-069 supports remote management

DIMENSIONS

- L: 11 cm; H: 3 cm; W: 9,6 cm



POWER REQUIREMENTS

- Input: 12VDC, 1A

OPERATING ENVIRONMENT

- Operating temperature: 0-40 °C
- Storage temperature: -20-70 °C
- Humidity: 20-95 % non-condensing

NETWORKING

- RFC-1483/2684 LLC/VC-Mux bridge/routed mode
- PPP over Ethernet (PPPoE)
- PPP over ATM (PPPoA)
- 1483 bridge, MER and routed Mode, IPoA, DS-Lite mode
- MAC Encapsulation Routing
- NAT Static Port Mappings, NAT/NAPT
- IGMP Proxy/Snooping
- DHCP Client, DHCP Server
- Dynamic DNS
- Static Routing, RIP v1/v2
- IPv6 supported
- TR069 supported