

802.11B/G/N 300MBPS WIRELESS VDSL2 ROUTER

(Artikel-Nr. 0338831V)



HARDWARE INTERFACE

- DC Power Jack
- Power switch to power on/off device
- Reset button to factory defaults
- RJ11 phone jacks for VDSL/ADSL connection
- 4x LAN:10/100Mbps Auto-MDI/MDI-X RJ-45 Ethernet port
- 2 external none-detachable Antennas
- WIFI On/Off button
- WPS (Wireless Protection System) button
- CE/ROHS compliant



OPERATING ENVIRONMENT

- Operating temperature: 0-40 °C
- Storage temperature: -20-70 °C
- Humidity: 20-95 % non-condensing

ADSL2+ COMPLIANCE

- Compliant with ADSL/ADSL2/ADSL2+ Standard
- Supports Annex A or Annex B
- Support 8 PVC

FEATURES

- IGMP snooping and IGMP proxy
- IPv4/IPv6 dual stacks function
- VPN pass through
- Management - HTTP Web-based configuration
- Remote Management-TR069/HTTP

WIFI-SPECIFICATION

- Operating Frequency : 2.412G~2.484GHz
- Supports 802.11b data rates of up to 11 Mbps with automatic fallback to 5.5, 2 and 1 Mbps
- Supports 802.11g data rates of up to 54 Mbps with automatic fallback to 48, 36, 24, 18, 12, 9 and 6 Mbps
- Supports 802.11n (MIMO 2T2R): Up to 300Mbps (MC515)
- Security supports 64/128-bits WEP, WPA, WPA2 and WPS
- Multi SSID

VDSL2 COMPLIANCE

- Compliant with VDSL2 Standard
- ITU-T G.994.1 and G.997.1
- VDSL2 Profiles: 8a, 8b, 8c, 8d, 12a, 12b, 17a, 30a
- Supports Annex A or Annex B
- 802.1p VLAN ID supported
- Backward compatible with ADSL2+

LAN SPECIFICATION

- LAN: 10 / 100Mbps Auto-MDI / MDI-X RJ-45 Ethernet port

Dimensions: L: 14 cm; H: 3 cm; W: 13 cm